

U.S. Serial No. 09/933,987

CLAIM AMENDMENTS:

1. (Previously presented) An OLED device structure comprising:

a substrate;

an OLED display area comprising a plurality of active pixels which are disposed over said substrate and which comprise an anode region, a cathode region and a light-emitting region;

a cover over said OLED display area, wherein said cover permits transmission of light from said active pixels to an outer environment, and wherein said cover and said substrate cooperate to restrict transmission of oxygen and water vapor from said outer environment to said OLED display area; and

a patterned getter layer disposed between said substrate and said cover, said patterned getter layer being configured so as to substantially avoid obstructing said transmission of light that is permitted by said cover from said pixels to said outer environment, wherein at least a portion of said patterned getter layer is provided between at least some of said plurality of pixels.

2. (Original) The OLED device structure of claim 1, wherein said patterned getter layer is provided on said substrate.

3. (Original) The OLED device structure of claim 1, wherein said patterned getter layer is provided on said cover.

4. (Previously presented) The OLED device structure of claim 1, wherein a portion of said patterned getter layer is provided at a position that is laterally beyond said OLED display area.

5. (Previously presented) The OLED device structure of claim 4, wherein a portion of said patterned getter layer is provided in the form of a ring that laterally surrounds said OLED display area.

U.S. Serial No. 09/933,987

6. (Canceled)

7. (Original) The OLED device structure of claim 1, wherein said patterned getter layer comprises at least one material selected from Group IIA metals and Group IIA metal oxides.

8. (Original) The OLED device structure of claim 1, wherein said patterned getter layer comprises at least one material selected from calcium metal, barium metal, calcium oxide and barium oxide.

9. (Currently amended) The OLED device structure of claim 1, wherein said OLED device structure is a flexible OLED device structure, and wherein portions of said patterned getter layer are sufficiently narrow to prevent said patterned getter layer from cracking when said OLED device structure is flexed during normal service.

10. (Cancelled)

11. (Cancelled)

12. (Original) The OLED device structure of claim 1, wherein said light emitting region comprises a hole transporting layer, an emission layer and an electron transporting layer.

13. (Original) The OLED device structure of claim 1, wherein said substrate, said anode region and said cathode region each permits transmission of light between said light-emitting region and said outer environment.

14. (Previously presented) The OLED device structure of claim 1, wherein said anode region is disposed under said light-emitting region, and wherein said cathode is disposed over said light-emitting region and permits transmission of light between said light-emitting region and said outer environment.

U.S. Serial No. 09/933,987

15. (Previously presented) The OLED device structure of claim 1, wherein said cathode region is disposed under said light-emitting region, and wherein said anode is disposed over said light-emitting region and permits transmission of light between said light-emitting region and said outer environment.

16. (Original) The OLED device structure of claim 1, further comprising a sealing region disposed between said substrate and said cover, said sealing region cooperating with said substrate and said cover to enclose said OLED display area and restrict transmission of water and oxygen from an outer environment to said OLED display area.

17. (Previously presented) A method of making an OLED device structure comprising:

- providing a substrate;

- forming an OLED display area over said substrate, said OLED display area comprising a plurality of active pixels that comprise an anode region, a cathode region and a light-emitting region;

- providing a cover over said OLED display area, wherein said cover permits transmission of light from said active pixels to an outer environment, and wherein said cover and said substrate cooperate to restrict transmission of oxygen and water vapor from said outer environment to said OLED display area; and

- providing a patterned getter layer between said substrate and said cover, said patterned getter layer being configured so as to substantially avoid obstructing said transmission of light that is permitted by said cover from said pixels to said outer environment, wherein at least a portion of said patterned getter layer is provided between at least some of said plurality of pixels.

18. (Original) The method of claim 17, wherein said patterned getter layer comprises a metal, and wherein said patterned getter layer is provided by vacuum deposition through a masking layer.

U.S. Serial No. 09/933,987

19. (Original) The method of claim 17, wherein said patterned getter layer comprises a metal oxide, and wherein said patterned getter layer is provided by applying a getter material in the form of a paste.

20. (Original) The method of claim 19, wherein said paste is applied by a technique selected from screen-printing and extrusion.

21-25. (Canceled)

26. (Previously presented) A flexible OLED device structure comprising:

a flexible substrate;

a flexible OLED display area comprising a plurality of active pixels disposed over said substrate, which comprise an anode region, a cathode region and a light-emitting region;

a flexible cover over said OLED display area, wherein at least one of said flexible substrate and said flexible cover permits transmission of light from said plurality of active pixels to an outer environment, and wherein said flexible cover and said flexible substrate cooperate to restrict transmission of oxygen and water vapor from said outer environment to said OLED display area; and

a patterned getter layer disposed between said flexible substrate and said flexible cover, wherein said patterned getter layer is configured so as to substantially avoid obstructing said transmission of light from said plurality of active pixels to said outer environment, wherein at least a portion of said patterned getter layer is provided between at least some of said plurality of pixels.

27. (Original) The flexible OLED device structure of claim 26, wherein at least one of said flexible substrate and said flexible cover comprises a composite barrier region, said composite barrier region further comprising two or more planarizing layers and two or more high-density layers.

U.S. Serial No. 09/933,987

28. (Original) The flexible OLED device structure of claim 26, wherein said patterned getter layer comprises at least one material selected from Group IIA metals and Group IIA metal oxides.

29. (Original) The flexible OLED device structure of claim 26, wherein portions of said patterned getter layer are sufficiently narrow to prevent said patterned getter layer from cracking when said OLED device structure is flexed during normal service.

30. (Previously presented) A flexible OLED device structure comprising:

a flexible substrate;

a flexible OLED display area comprising a plurality of active pixels disposed over said substrate, each of said plurality of active pixels comprising an anode region, a cathode region and a light-emitting region;

a flexible cover over said OLED display area, wherein at least one of said flexible substrate and said flexible cover permits transmission of light from said plurality of active pixels to an outer environment, and wherein said flexible cover and said flexible substrate cooperate to restrict transmission of oxygen and water vapor from said outer environment to said OLED display area; and

a patterned getter layer disposed between said flexible substrate and said flexible cover, said patterned getter layer being configured so as to substantially avoid obstructing said transmission of light from said plurality of active pixels to said outer environment, wherein portions of said patterned getter layer are sufficiently narrow to prevent said patterned getter layer from cracking when said OLED device structure is flexed during normal service and wherein said patterned getter layer comprises a plurality of narrow bands of getter material.

31. (Currently amended) The flexible OLED device structure of claim 29, wherein said patterned getter layer comprises a plurality of small-dots of getter material.

32. (Original) The flexible OLED device structure of claim 26, wherein a portion of said patterned getter layer is provided adjacent to each of said plurality of pixels.

U.S. Serial No. 09/933,987

33. (Previously presented) The flexible OLED device structure of claim 26, wherein said flexible substrate and said flexible cover each comprises a composite barrier region that further comprises two or more planarizing layers and two or more high-density layers.

34. (Previously presented) The flexible OLED device structure of claim 26, wherein said flexible cover comprises a composite barrier region that further comprises two or more planarizing layers and two or more high-density layers.

35. (Previously presented) The flexible OLED device structure of claim 34, wherein said flexible cover further comprises a substrate-sublayer.

36. (Cancelled)

37. (Previously presented) The flexible OLED device structure of claim 26, wherein said flexible substrate comprises a metal foil.

38. (Previously presented) The flexible OLED device structure of claim 26, wherein said substrate, said anode region and said cathode region each permits transmission of light between said light-emitting region and said outer environment.

39. (Previously presented) The flexible OLED device structure of claim 26, wherein said anode region is disposed under said light-emitting region, and wherein said cathode is disposed over said light-emitting region and permits transmission of light between said light-emitting region and said outer environment.

40. (Previously presented) The flexible OLED device structure of claim 26, wherein said cathode region is disposed under said light-emitting region, and wherein said anode is disposed over said light-emitting region and permits transmission of light between said light-emitting region and said outer environment.

U.S. Serial No. 09/933,987

41. (Canceled)

42. (Currently amended) The OLED device structure of claim 1, wherein said patterned getter layer comprises a plurality of narrow bands of getter material or a plurality of ~~small~~ dots of getter material.

43. (Previously presented) The OLED device structure of claim 1, wherein said OLED device structure is a top emission OLED device structure.

44. (Previously presented) The OLED device structure of claim 43, wherein said top emission OLED device structure is a flexible top emission OLED device structure.

45. (Previously presented) The method of claim 17, wherein said OLED device structure is a top emission OLED device structure.

46. (Previously presented) The method of claim 45, wherein said top emission OLED device structure is a flexible top emission OLED device structure.